

Industrial Gear Units

Technology for Conveying Systems



Complete drive systems for your conveying applications

Excellent performance needs a strong partner – SEW-EURODRIVE has been supplier of drive technology for many decades, and now is among the leading companies for drive technology worldwide. Whatever your requirements are, the application experts from SEW-EURODRIVE can provide you with the optimum drive package solution. Our offering not only includes the single components such as gear units, couplings or brakes, but the complete system that precisely fits your needs.

You need a customized solution?

You can rely on us from project planning to commissioning and operation. We are dedicated to supporting you in keeping the total cost of ownership of your conveying system at the lowest possible level. No matter whether you need

technical calculations, specific documentation, such as quality certificates or project-specific operating instructions, condition monitoring or service on site – SEW-EURODRIVE is your partner.





Our solutions for:

Belt conveyors	4
Bucket elevators	10
Apron feeders	16

Our drive solution for belt conveyors



SEW-EURODRIVE offers suitable industrial gear units for belt conveying systems requiring high torque ratings. Even under severe conditions such as high ambient temperatures, our modular design with a specific housing concept offers an optimum solution for these kinds of applications.

Size and torque capacity

X.K.. bevel-helical gear units: 3 stages, gear ratio $i = 12.5 \dots 90$

Gear unit size	Torque class M_{N2} [kNm]
180	58
190	65
200	79
210	90
220	112
230	131
240	156
250	175
260	205
270	240
280	270
290	308
300	350
310	425
320	475

Features

- Application gear unit made of proven components of X series products
- 3-stage bevel gear unit with dedicated horizontal housing for extended heat dissipation
- Enhanced cooling capacity with efficient fan concept
- Wide range of available accessories from the standard X series

Benefits


- Efficient cooling concept eliminates the use of external cooling devices and of a bigger gear unit
- Reliable solution for rough environments



Wide range of available features

Many features of the modular standard X series products can be combined with this application gear unit

**Efficient sealing system,
for example Taconite**



**Gray cast (GG25) housing with extend-
ed surface for better heat dissipation**



Rigid flange coupling



Versatile shaft concepts



Solid shaft with keyway
(or smooth type)




Splined solid shaft



Hollow shaft with keyway
(or splined hollow shaft)




Hollow shaft for shrink
disk connection




**Standard backstop or
torque limiting backstop**



Axial fan for optimal cooling




Pressure lubrication with shaft end pump or splash lubrication



Many more options are available for the drive package


- Inclined mounting position
- Suitable for using an auxiliary drive
- Oil dipstick / oil level glass
- Oil drain, optional
- Oil bath temperature sensor PT100
- Des-Case breather, optional
- Swing base / base frame design
- Brakes
- Mechanical couplings
- Fluid couplings
- ATEX on request





Thermal housing

Gear unit size	A	B	CFA	ø D	ø D1	ø EB	ø ES	F	H	IF	IF1	JF	L	L1	LFA
180	544	600	90	170 _{m6}	70 _{m6}	210	140	46	435 _{-0.5}	453	357	379	300	140	85
190	576	600	90	170 _{m6}	70 _{m6}	210	140	46	435 _{-0.5}	453	357	379	300	140	85
200	614	630	116	180 _{m6}	80 _{m6}	245	140	55	485 _{-0.5}	499	402	424	300	170	113
210	650	630	116	190 _{m6}	80 _{m6}	245	140	55	485 _{-0.5}	499	402	424	350	170	113
220	694	710	105	210 _{m6}	85 _{m6}	290	140	65	550 _{-0.5}	560	467	467	350	170	102
230	734	710	105	230 _{m6}	85 _{m6}	290	140	65	550 _{-0.5}	560	467	467	410	170	102
240	776	840	138	230 _{m6}	100 _{m6}	290	140	68	600 _{-0.5}	595	509	507	410	210	130
250	799	840	138	240 _{m6}	100 _{m6}	290	140	68	600 _{-0.5}	595	509	507	410	210	130
260	855	920	125	250 _{m6}	110 _{m6}	322	140	80	720 _{-0.5}	640	620	554	410	210	122
270	890	920	125	270 _{m6}	110 _{m6}	322	140	80	720 _{-0.5}	640	620	554	470	210	122
280	942	920	125	290 _{m6}	110 _{m6}	322	140	80	800 _{-0.5}	685	685	554	470	210	122
290	987	1000	127	290 _{m6}	120 _{m6}	412	140	80	850 _{-0.5}	735	747	604	470	210	122
300	1016	1000	127	300 _{m6}	120 _{m6}	412	140	80	850 _{-0.5}	735	747	604	470	210	122
310	1100	1120	171	320 _{m6}	130 _{m6}	420	140	85	950 _{-0.5}	795	827	659	470	250	165
320	1134	1120	171	340 _{m6}	130 _{m6}	420	140	85	950 _{-0.5}	795	827	659	550	250	165

X3KS../HT

LG	LH	LK	OS	P	ø S (6x)	T	T1	U	U1	V	V1	V2	V3	WB	WS max.	Weight [kg]	Oil volume (splash lubrication) [l]
1460	1135	1735	592	862	42	179	74.5	40 _{h9}	20 _{h9}	510	675	305	165	360	468	1705	110
1460	1167	1735	592	862	42	179	74.5	40 _{h9}	20 _{h9}	510	707	273	197	360	468	1790	110
1642	1286	1962	612	930	48	190	85	45 _{h9}	22 _{h9}	540	759	481	74	394	503.5	2350	162
1642	1322	1962	662	930	48	200	85	45 _{h9}	22 _{h9}	540	795	445	110	394	503.5	2415	162
1835	1430	2170	703	1056	48	221	90	50 _{h9}	22 _{h9}	590	885	525	180	428	538.5	3340	216
1835	1470	2170	763	1056	48	241	90	50 _{h9}	22 _{h9}	590	925	485	220	428	538.5	3465	216
1972	1597	2363	811	1143	56	241	106	50 _{h9}	28 _{h9}	720	987	578	282	472	583.5	4400	301
1972	1620	2363	811	1143	56	252	106	56 _{h9}	28 _{h9}	720	1010	555	305	472	583.5	4500	301
2181	1767	2620	847	1308	56	262	116	56 _{h9}	28 _{h9}	800	1095	645	345	563	598.5	5915	474
2181	1802	2620	920	1308	56	282	116	63 _{h9}	28 _{h9}	800	1130	610	380	563	598.5	6315	474
2260	1854	2701	920	1433	56	302	116	63 _{h9}	28 _{h9}	800	1190	610	380	563	598.5	6965	549
2484	2021	2967	962	1533	65	302	127	63 _{h9}	32 _{h9}	880	1311	689	311	610	639.5	8390	733
2484	2050	2967	962	1533	65	314	127	70 _{h9}	32 _{h9}	880	1340	660	340	610	639.5	9035	733
2751	2135	3225	999	1693	65	334	137	70 _{h9}	32 _{h9}	980	1371	784	371	688	672	10785	1013
2751	2169	3225	1079	1693	65	355	137	80 _{h9}	32 _{h9}	980	1405	750	405	688	672	11610	1013

Our drive solution for bucket elevators



For your bucket elevator systems, SEW-EURODRIVE offers a standardized application gear unit based on the reliable components of the X series and 7 series gear units. The slow movements required for maintenance purposes can be realized according to your needs. Our solution is available as “empty bucket” and “full bucket” version.

Size and torque capacity

X3K.B... bevel-helical gear units: 3 stages, gear ratio $i = 28$ to 80

Gear unit size	Torque class M_{N2} [kNm]
100	6.8
110	8.5
120	12.8
130	16
140	22
150	27.5
160	36
170	45
180	58
190	65
200	79
210	90
220	112
230	131
240	156
250	175
260	205
270	240
280	270

Features

- Based on the X series with predefined drive components
- Auxiliary drive with the proven SEW-EURODRIVE gearmotor
- Auxiliary drive adapter with overrunning clutch and incremental encoder
- Mounted backstop
- Radial labyrinth seal on input and output shafts

Benefits

- All drive components are perfectly matched
- Safety through speed monitoring
- High availability due to modular concept
- Wide range of accessory equipment available upon request




Wide range of available features

Our application gear unit for bucket elevator applications is based on the standardized combination of X series gear units with a gearmotor as auxiliary drive.

Powerful fan solutions




Oil monitoring




Oil temperature monitoring






**Auxiliary drive
with overrunning clutch**



**Efficient sealing concepts
like Taconite**



Versatile shaft concepts



Hollow shaft with key or shrink disk



Solid shaft with or without key


Many more options
are available for
the drive package

- Splash / pressure lubrication
- Inclined mounting positions
- Rigid flange coupling
- Backstop
- Torque limiting backstop
- Des-Case breather
- Brakes
- Mechanical couplings
- Fluid couplings
- Swing bases / base frame design
- ATEX on request



Bucket elevator

Gear unit size	A	B	ø D	ø D1	ø EB	F	H	L	L1	LA	LG	LH	LK	OS
100	278	260	80 _{m6}	32 _{k6}	133	29	190 _{-0.5}	170	80	190 _{-0.5}	658	632	822	343
110	298	260	90 _{m6}	32 _{k6}	133	29	190 _{-0.5}	170	80	215 _{-0.5}	703	652	867	346
120	327	300	100 _{m6}	38 _{k6}	153	33	225 _{-0.5}	210	100	215 _{-0.5}	767	745	960	401
130	363	300	110 _{m6}	38 _{k6}	153	33	225 _{-0.5}	210	100	250 _{-0.5}	838	781	1031	404
140	388	360	120 _{m6}	50 _{k6}	175	42	265 _{-0.5}	250	110	250 _{-0.5}	903	879	1129	432
150	430	360	130 _{m6}	50 _{k6}	175	42	265 _{-0.5}	250	110	295 _{-0.5}	990	921	1216	475
160	474	425	140 _{m6}	60 _{m6}	190	50	315 _{-0.5}	300	140	355 _{-0.5}	1144	1036	1391	506
170	525	425	160 _{m6}	60 _{m6}	190	50	315 _{-0.5}	300	140	355 _{-0.5}	1195	1087	1442	556
180	544	475	170 _{m6}	70 _{m6}	210	55	335 _{-0.5}	300	140	370 _{-0.5}	1249	1135	1505	592
190	576	475	170 _{m6}	70 _{m6}	210	55	335 _{-0.5}	300	140	370 _{-0.5}	1281	1167	1537	592
200	614	515	180 _{m6}	80 _{m6}	210	60	375 _{-0.5}	300	170	420 _{-0.5}	1409	1286	1706	612
210	650	515	190 _{m6}	80 _{m6}	210	60	375 _{-0.5}	350	170	420 _{-0.5}	1445	1322	1742	662
220	694	540	210 _{m6}	85 _{m6}	245	62	425 _{-0.5}	350	170	465 _{-0.5}	1584	1430	1895	703
230	734	540	230 _{m6}	85 _{m6}	245	62	425 _{-0.5}	410	170	465 _{-0.5}	1624	1470	1935	763
240	776	625	230 _{m6}	100 _{m6}	290	68	450 _{-0.5}	410	210	495 _{-0.5}	1721	1597	2092	811
250	799	625	240 _{m6}	100 _{m6}	290	68	450 _{-0.5}	410	210	495 _{-0.5}	1744	1620	2115	811
260	855	705	250 _{m6}	110 _{m6}	288	73	500 _{-0.5}	410	210	545 _{-0.5}	1900	1767	2312	847
270	890	705	270 _{m6}	110 _{m6}	288	73	500 _{-0.5}	470	210	545 _{-0.5}	1935	1802	2347	920
280	942	705	290 _{m6}	110 _{m6}	288	73	555 _{-0.5}	470	210	610 _{-0.5}	2052	1854	2464	920

X3KS..

P	$\varnothing S$	T	T1	U	U1	V	V1	V2	V3	WB	Y	Y1	Y2	Y3	Y4
380	24 (4x)	85	35	22 _{h9}	10 _{h9}	210	370	90	-	213	679	65	146	403	494
380	24 (4x)	95	35	22 _{h9}	10 _{h9}	210	390	115	-	213	679	65	166	423	494
450	28 (4x)	106	41	28 _{h9}	10 _{h9}	245	440	105	-	235	750	100	187	452	535
450	28 (4x)	116	41	28 _{h9}	10 _{h9}	245	475	140	-	235	750	100	223	488	535
530	35 (4x)	127	53.5	32 _{h9}	14 _{h9}	290	510	110	-	284	880	115	208	538	633
530	35 (4x)	137	53.5	32 _{h9}	14 _{h9}	290	555	115	-	284	880	115	250	580	633
630	42 (4x)	148	64	36 _{h9}	18 _{h9}	340	620	185	-	320	1030	140	262	649	735
630	42 (4x)	169	64	40 _{h9}	18 _{h9}	340	670	185	-	320	1030	140	313	700	735
670	42 (6x)	179	74.5	40 _{h9}	20 _{h9}	390	710	190	215	360	1115	110	279	769	860
670	42 (6x)	179	74.5	40 _{h9}	20 _{h9}	390	740	190	215	360	1115	110	311	801	860
750	48 (6x)	190	85	45 _{h9}	22 _{h9}	420	780	205	230	381	1224	150	349	839	879
750	48 (6x)	200	85	45 _{h9}	22 _{h9}	420	815	205	230	381	1224	150	385	875	879
850	48 (6x)	221	90	50 _{h9}	22 _{h9}	440	910	250	280	426	1392	200	379	919	983
850	48 (6x)	241	90	50 _{h9}	22 _{h9}	440	950	250	280	426	1392	200	419	959	983
900	56 (6x)	241	106	50 _{h9}	28 _{h9}	510	990	250	305	472	1524	175	401	1051	1158
900	56 (6x)	252	106	56 _{h9}	28 _{h9}	510	1010	250	305	472	1524	175	424	1074	1158
1000	56 (6x)	262	116	56 _{h9}	28 _{h9}	590	1110	300	350	553	1574	225	480	1130	1235
1000	56 (6x)	282	116	63 _{h9}	28 _{h9}	590	1110	300	350	553	1574	225	515	1165	1235
1110	56 (6x)	302	116	63 _{h9}	28 _{h9}	590	1190	360	380	553	1629	280	567	1217	1235

Our drive solution for apron feeders



SEW-EURODRIVE offers planetary gear units optimized for apron feeders for use in the mining industry, such as for iron ore, coal, gold, diamond and mineral sand mining. These planetary gear units are characterized by a robust design and meet demanding criteria for high durability and low maintenance.

Solutions for medium-size apron feeders

The compact P series with its ideal power output offers a wide range of useful options for apron conveyors. The elaborate modular concept with

a drive unit consisting of gearmotor and planetary gear unit allow for maximum flexibility regarding torque and gear ratio.

Size and torque capacity

Gear unit size	IE3 motor size	Nom. torque [kNm]	Ratio range
PHF002 KF77	DRP132MC4	24	140–619
PHF012 KF87	DRP160MC4	36	291–683
PHF022 KF97	DRP180ML4	51	241–543
PHF032 KF97	DRP200L4	69	241–543
PHF042 KF107	DRP225S4	100	341–547
PHF052 KF127	DRP225M4	124	341–563
PHF062 KF127	DRP225M4	185	421–830
PHF072 KF127	DRP225M4	245	677–1195
PHF082 KF157	DRP225M4	359	899–1756
PHF092 KF167	DRP315K4	423	405–915
PHF102 KF187	DRP315M4	500	341–660

Features and benefits of the P series

Features

Planetary gear units P series ...

- can transmit high torque
- are very compact
- offer high torsional rigidity

Gearmotors ...


- offer a large variance on the input side
- are available in their respective gear ratio range
- can be combined with planetary gear units in helical or bevel-helical designs


Benefits

- Perfectly matching units (gear unit and motor)
- Large range of options due to the SEW-EURODRIVE modular concept
- Short, compact design because there is no need for couplings and adapter flanges
- Standardized units mean excellent price/performance ratio and short delivery times



Wide range of available features





Output shafts




Solid shaft
with keyway



Hollow shaft for
shrink fit connection

Torque arm



Oil temperature monitoring



Taconite sealing system for extremely dusty atmospheres




Energy-efficient motor IE2/IE3





Planetary gear units

Gear unit		IE3 motor/ size	A	B	ø B1	C1	ø D	ø D6	ø D17	ø D18	ø E1	F1
PHF002	KF77	DRP132MC4	650	704	330 _{f9}	39.5	110 ^{H8}	120 ^{H7}	110 _{g7}	120 _{h6}	370	4
PHF012	KF87	DRP160MC4	700	785	370 _{f9}	41.5	130 ^{H8}	140 ^{H7}	130 _{g7}	140 _{h6}	410	4
PHF022	KF97	DRP180LC4	750	906	410 _{f9}	48	140 ^{H8}	150 ^{H7}	140 _{g7}	150 _{h6}	460	5
PHF032	KF97	DRP200L4	800	967	460 _{f9}	50	155 ^{H8}	165 ^{H7}	155 _{g7}	165 _{g6}	510	5
PHF042	KF107	DRP225S4	900	1056	480 _{f9}	64	180 ^{H8}	190 ^{H7}	180 _{g7}	190 _{g6}	560	5
PHF052	KF127	DRP225M4	1000	1162	530 _{f9}	64	200 ^{H8}	210 ^{H7}	200 _{g7}	210 _{g6}	590	5
PHF062	KF127	DRP225M4	1200	1232	610 _{f9}	74	230 ^{H8}	240 ^{H7}	230 _{g7}	240 _{g6}	690	5
PHF072	KF157	DRP250M4	1500	1398	690 _{f9}	84	250 ^{H8}	260 ^{H7}	250 _{g7}	260 _{g6}	770	8
PHF082	KF157	DRP250M4	1600	1473	750 _{f9}	84	280 ^{H8}	290 ^{H7}	280 _{g7}	290 _{g6}	840	8
PHF092	KF167	DRP315K4	1650	1721.5	800 _{f9}	90	300 ^{H8}	310 ^{H7}	300 _{g7}	310 _{g6}	870	10
PHF102	KF187	DRP315K4	1700	1826.5	850 _{f9}	100	330 ^{H8}	340 ^{H7}	330 _{g7}	340 _{g6}	960	10


PHF.. KF..

FT	ø G	I2	LT	M4	M5	M6	M7	P	ø S1	ø AC	AD	L	LB
25	410	165	880	103	35	46	80	286	22 (16x)	221	170	836	429
30	450	170	955	108	32	45	85	338	22 (20x)	270	228	947	465
35	500	180	1035	108	34	45	85	414	22 (24x)	316	253	1116	589
35	560	210	1125	136	39	55	110	414	26 (20x)	394	283	1219	662
40	620	255	1270	146	45	65	115	500	33 (20x)	394	283	1357	706
40	650	275	1390	163	47	75	125	592	33 (24x)	394	283	1406	691
50	760	295	1655	187	53	80	150	592	39 (24x)	394	283	1461	691
60	840	320	2020	201	55	85	160	705	39 (24x)	510	397	1617	771
70	920	340	2160	207	56	80	170	705	45 (24x)	511	397	1657	771
70	950	380	2235	218	65	95	175	786	45 (20x)	624	506	1938	941
70	1050	420	2335	255	65	100	205	942	45 (24x)	624	506	2057	941

Solutions for large-size apron feeders

The P-X gear units with outstanding thermal power are the ideal solution for mid-range torque applications.

Our XP gear units offer highest torque capacity and a long service life even for tough applications.



P-X gear units

- Torque up to 500 kNm
- Ratio from $i = 140 \dots 500$

Features and benefits of P-X gear units and the XP series

Features


Maximum power planetary gear units

- Transmission of highest torque
- Suitable for high motor power
- Wide ratio range
- Variable cooling system
- Different coupling variants

Benefits

Maximum power planetary gear units

- Customized product
- Free choice of accessories and options



XP series

- Torque from 500 kNm to 5200 kNm
- Ratio from $i = 140 \dots 500$

SEW-EURODRIVE is right there for you:

Argentina

Tel. +54 3327 4572-84
Fax +54 3327 4572-21
sewar@sew-eurodrive.com.ar

Australia

Tel. +61 3 9933-1000
Fax +61 3 9933-1003
enquires@sew-eurodrive.com.au

Austria

Tel. +43 1 617 55 00-0
Fax +43 1 617 55 00-30
sew@sew-eurodrive.at

Belarus

Tel. +375 17 298 47 56
Fax +375 17 298 47 54
sales@sew.by

Belgium

Tel. +32 16 386-311
Fax +32 16 386-336
info@sew-eurodrive.be

Brazil

Tel. +55 19 3835-8000
sew@sew.com.br

Canada

Tel. +1 905 791-1553
Fax +1 905 791-2999
marketing@sew-eurodrive.ca

Chile

Tel. +56 2 2757 7000
Fax +56 2 2757 7001
ventas@sew-eurodrive.cl

China

Tel. +86 22 25322612
Fax +86 22 25323273
info@sew-eurodrive.cn

Colombia

Tel. +57 1 54750-50
Fax +57 1 54750-44
sew@sew-eurodrive.com.co

Czech Republic

Tel. +420 255 709 601
Fax +420 235 350 613
sew@sew-eurodrive.cz

Denmark

Tel. +45 43 9585-00
Fax +45 43 9585-09
sew@sew-eurodrive.dk

Finland

Tel. +358 201 589-300
Fax +358 3 7806-211
sew@sew.fi

France

Tel. +33 3 88 73 67 00
Fax +33 3 88 73 66 00
sew@usocome.com

Great Britain

Tel. +44 1924 893-855
Fax +44 1924 893-702
info@sew-eurodrive.co.uk

Hong Kong

Tel. +852 36902200
Fax +852 36902211
contact@sew-eurodrive.hk

Hungary

Tel. +36 1 437 06-58
Fax +36 1 437 06-50
office@sew-eurodrive.hu

India

Tel. +91 265 3045200
Fax +91 265 3045300
marketing@seweurodriveindia.com

Italy

Tel. +39 02 96 9801
Fax +39 02 96 980 999
sewit@sew-eurodrive.it

Ivory Coast

Tel. +225 21 21 81 05
Fax +225 21 25 30 47
info@sew-eurodrive.ci

Japan

Tel. +81 538 373811
Fax +81 538 373814
sewjapan@sew-eurodrive.co.jp

Kazakhstan

Tel. +7 727 238 1404
Fax +7 727 243 2696
sew@sew-eurodrive.kz

Malaysia

Tel. +60 7 3549409
Fax +60 7 3541404
sales@sew-eurodrive.com.my

Mexico

Tel. +52 442 1030-300
Fax +52 442 1030-301
scmexico@seweurodrive.com.mx

Mongolia

Tel. +976 77109997
Fax +976 77109997
sew@sew-eurodrive.mn

Morocco

Tel. +212 523 32 27 80/81
Fax +212 523 32 27 89
sew@sew-eurodrive.ma

Netherlands

Tel. +31 10 4463-700
Fax +31 10 4155-552
info@sew-eurodrive.nl

New Zealand

Tel. +64 9 2745627
Fax +64 9 2740165
sales@sew-eurodrive.co.nz

Norway

Tel. +47 69 241-020
Fax +47 69 241-040
sew@sew-eurodrive.no

Paraguay

Tel. +595 991 519695
Fax +595 21 3285539
sewpy@sew-eurodrive.com.py

Peru

Tel. +51 1 3495280
Fax +51 1 3493002
sewperu@sew-eurodrive.com.pe

Poland

Tel. +48 42 676 53 00
Fax +48 42 676 53 49
sew@sew-eurodrive.pl

Portugal

Tel. +351 231 20 9670
Fax +351 231 20 3685
info@sew@sew-eurodrive.pt

Russia

Tel. +7 812 3332522
Fax +7 812 3332523
sew@sew-eurodrive.ru

Singapore

Tel. +65 68621701
Fax +65 68612827
sewsingapore@sew-eurodrive.com

Slovakia

Tel. +421 2 33595 202
Fax +421 2 33595 200
sew@sew-eurodrive.sk

South Africa

Tel. +27 11 248 7000
Fax +27 11 248 7289
info@sew.co.za

South Korea

Tel. +82 31 492-8051
Fax +82 31 492-8056
master.korea@sew-eurodrive.com

Spain

Tel. +34 94 4318470
Fax +34 94 4318471
sew.spain@sew-eurodrive.es

Sweden

Tel. +46 36 3442 00
Fax +46 36 3442 80
info@sew-eurodrive.se

Switzerland

Tel. +41 61 41717-17
Fax +41 61 41717-00
info@imhof-sew.ch

Tanzania

Tel. +255 22 277 5780
Fax +255 22 277 5788
uroos@sew.co.tz

Thailand

Tel. +66 38 454281
Fax +66 38 454288
sewthailand@sew-eurodrive.com

Turkey

Tel. +90 262 999 1000-04
Fax +90 262 999 1009
sew@sew-eurodrive.com.tr

Ukraine

Tel. +380 56 370 3211
Fax +380 56 372 2078
sew@sew-eurodrive.ua

Uruguay

Tel. +598 2 2118189
Fax +598 2 2118190
sewuy@sew-eurodrive.com.uy

USA

Tel. +1 864 439-7537
Fax +1 864 439-7830
cslyman@seweurodrive.com

Venezuela

Tel. +58 241 832-9804
Fax +58 241 838-6275
ventas@sew-eurodrive.com.ve

How we're driving the world



SEW-EURODRIVE
Driving the world

Fast. Up-to-date. Online: www.driveworld.de/en